

AT 54-532FLS

150MM WHEAT BOA BOOT



STYLE SPECIFICATIONS



DESCRIPTION:

All terrain 100% waterproof premium nubuck leather composite toe cap safety boot.

Colour: Wheat

Sizes: 3 - 15, 6 ½ - 12 ½ (UK/AUS)

Standards:

AS/NZS 2210.3:2019

EN ISO 20345:2022

AMD 1:2024

CE Marking: EN ISO 20345:2022 + A1:2024, S2 HI CI FO AN SC LG HRO SR

Application: Agriculture / Building & Construction / Manufacturing / Metals Industry / Mining & Quarrying / Oil & Gas / Transport & Storage / Security / Warehousing



FEATURES:

- BOA® Fit System delivers micro-adjustable, precision fit, engineered and guaranteed to perform in the toughest conditions
- ANKLEshield® Technology delivers superior ankle protection for enhanced stability and confidence on challenging terrain
- 100% waterproof premium nubuck leather
- Breathable, waterproof membrane layered under the leather for added protection
- TECtuff® toe bumper to protect against scuffing
- COOLstep® lining to absorb moisture and odour for optimum freshness and hygiene
- HEELguard for added stability and increased durability
- Heavy duty Kevlar® stitching across critical wear seams
- COMFORTcushion® Impact Absorption System Insole with PORON® protects the heel and ball of the foot
- NATUREform® composite toe cap with a wide profile for greater comfort
- Driver-centric stabiliser ensures optimised foot positioning for comfort and control while driving
- Certified ladder grip zones offer secure, slip-resistant footing on ladders for improved safety
- Enhanced lateral grip ensures stable footing and confidence during side-to-side movements
- Programmed deformation zones in the sole provide advanced cushioning and rebound, delivering extra shock absorption for all-day comfort
- Stop & hold technology delivers reliable steadiness on uneven or inclined surfaces, helping prevent slips and falls
- NANOlite® footbed with memory foam to help reduce fatigue
- Oliver SOFTstride® open cell low density urethane foam built-in to the insole for ultimate comfort and contour support
- Excellent slip resistant sole; SRC slip resistant classification. Anti-static
- AT's dual density PU/Rubber sole with lightweight shock absorbing PU midsole & hardwearing rubber outsole for superior durability. Resistant to 300 °C surface contact
- Deep tread profile, with a self-cleaning design delivers superior traction in the roughest of terrain
- Sole resistant to mineral & organic oils & acids. Cut, split and crack resistant

COMFORT TECHNOLOGY



COMFORTcushion
Impact
Absorption



NATUREform
wide profile Type
1 safety toe cap



Waterproof
footwear



Non-Metallic
Composite
Toecap



NANOlite
footbed



SOFTstride
Contour Comfort
Support



Antimicrobial
Technology



HEELguard



ANKLEshield®
Technology



BOA®
Fit System

SOLING TECHNOLOGY



300°C
Heat Resistant
sole (572° F)



Abrasion
Resistant sole



Cut Resistant
sole



Slip Resistant
sole



Sole resistant to
mineral oils
and acids



Sole resistant to
organic oils
and fats



Antistatic
discharges static
build-up

OLIVER FOOTWEAR

Level 5, 163-175 O'Riordan Street
Mascot, NSW, 2020

Tel: 1300 747 269
(1300 PIP ANZ)

Email: CS@PIPANZ.COM
www.oliver.com.au

PIP
GLOBAL SAFETY



Facebook.com/oliversafetyfootwear



@oliver.boots

© 2025 Protective Industrial Products, Inc.

